

Epson WorkForce Pro WF-7840DTWF Inkjet A3 4800 x 2400 DPI Wi-Fi

Brand : Epson

Product family: WorkForce Pro **Product code:** C11CH67402

Product name : WF-7840DTWF

A3+, Print, Scan, Copy, Fax, 4800 x 2400 DPI, USB, LAN, WLAN, Touchscreen, 20.6 kg
 Epson WorkForce Pro WF-7840DTWF. Print technology: Inkjet, Printing: Colour printing, Maximum resolution: 4800 x 2400 DPI. Scanning: Colour scanning, Optical scanning resolution: 1200 x 2400 DPI. Faxing: Colour faxing. Maximum ISO A-series paper size: A3. Wi-Fi. Product colour: Black



| Printing | | Paper handling | |
|-----------------------------------------------|------------------------------|------------------------------|----------------------------------------------------------------------------------------------------------|
| Duplex printing mode | Auto | Envelopes sizes | 10, C4, C6, DL |
| Print technology * | Inkjet | Photo paper sizes | 9x13,10x15,13x18 |
| Printing * | Colour printing | Paper tray media weight | 64 - 256 g/m ² |
| Duplex printing * | ✓ | Ports & interfaces | |
| Maximum resolution * | 4800 x 2400 DPI | USB port | ✓ |
| Print speed (ISO/IEC 24734) black | 25 ppm | Network | |
| Print speed (ISO/IEC 24734) colour | 12 ppm | Wi-Fi * | ✓ |
| Duplex print speed (ISO/IEC 24734, A4) black | 16 ppm | Ethernet LAN * | ✓ |
| Duplex print speed (ISO/IEC 24734, A4) colour | 9 ppm | Security algorithms | 64-bit WEP, 128-bit WEP, WPA-PSK, WPA-TKIP, WPA-AES |
| Borderless printing | ✓ | Management protocols | SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNT, SLP, WSD, LLTD, Ping |
| Scanning | | Mobile printing technologies | Epson Connect, Epson iPrint, Epson Email Print, Epson Remote Print, Apple AirPrint, Mopria Print Service |
| Duplex scanning * | ✓ | Performance | |
| Scanning * | Colour scanning | Card reader integrated | ✗ |
| Optical scanning resolution * | 1200 x 2400 DPI | Design | |
| Scan technology | CIS | Product colour * | Black |
| Scan to | Cloud | Market positioning * | Home & office |
| Image formats supported | BMP, JPEG, TIFF, PNG | Built-in display * | ✓ |
| Document formats supported | PDF | Display | LCD |
| Fax | | Display diagonal | 10.9 cm (4.3") |
| Faxing * | Colour faxing | Touchscreen | ✓ |
| Fax transmission speed | 3 sec/page | Colour display | ✓ |
| Modem speed | 33.6 Kbit/s | Power | |
| Fax memory | 550 pages | Power consumption (copying) | 20 W |
| Auto-redialing | ✓ | Power consumption (ready) | 8.8 W |
| Fax speed dialing (max numbers) | 200 | Power consumption (off) | 0.2 W |
| Fax forwarding to | E-mail, Folder, PC | Weight & dimensions | |
| Fax delayed sending | ✓ | Width | 515 mm |
| Error Correction Mode (ECM) | ✓ | Depth | 450 mm |
| Features | | Height | 350 mm |
| Maximum duty cycle * | 50000 pages per month | | |
| Number of print cartridges * | 4 | | |
| Printing colours * | Black, Cyan, Magenta, Yellow | | |
| Page description languages | ESC/P-R | | |

| Features | | Weight & dimensions | |
|-------------------------------------------|---------------------|--------------------------------|-------------------------------------------|
| Country of origin | Indonesia | Weight | 20.6 kg |
| Input & output capacity | | Packaging data | |
| Total number of input trays * | 3 | Package width | 524 mm |
| Total output capacity * | 125 sheets | Package depth | 589 mm |
| Auto document feeder (ADF) | ✓ | Package height | 457 mm |
| Auto document feeder (ADF) input capacity | 50 sheets | Package weight | 23.6 kg |
| Maximum input capacity | 550 sheets | Quantity per pack | 1 pc(s) |
| Paper handling | | Packaging content | |
| Maximum ISO A-series paper size * | A3 | Cartridge(s) included | ✓ |
| Paper tray media types * | Thick paper | Cables included | AC |
| ISO A-series sizes (A0...A9) * | A3, A3+, A4, A5, A6 | Warranty card | ✓ |
| ISO B-series sizes (B0...B9) | B5 | Logistics data | |
| Non-ISO print media sizes | Legal, Letter | Harmonized System (HS) code | 84433100 |
| | | Products per pallet layer | 2 pc(s) |
| | | Products per pallet | 8 pc(s) |
| | | Products per pallet layer (UK) | 2 pc(s) |
| | | Products per pallet (UK) | 8 pc(s) |
| | | Other features | |
| | | Printing method | Epson PrecisionCore |
| | | Number of users | 5 user(s) |
| | | Ink drop | 3.8 |
| | | Fax polling | ✓ |
| | | Print head nozzles | 800 nozzles black, 256 nozzles per colour |
| | | Supported network protocols | TCP/IPV4, TCP/IPV6 |



8715946668390

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-OCT-2024. Prints or copies of Information are only valid on the printed Publication date